



## General info

### Technical - Linear system

System composed of extruded aluminum profile and lighting elements with magnetic fixing. The system is available in black, white or satin brass color for ceiling, suspended or recessed installation.

|              |                                      |
|--------------|--------------------------------------|
| Ean          | 8021696282015                        |
| Item         | EGO TRACK DOUBLE 16W 3000K ON-OFF GD |
| Installation | Linear system                        |
| Guarantee    | 5 years                              |
| Gross weight | 0.44 kg                              |
| Volume       | 0.004092 m <sup>3</sup>              |

## Technical info

|                          |                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------|
| Net weight               | 0.26 kg                                                                           |
| Insulation class         | III                                                                               |
| Protection index         | IP20                                                                              |
| Compliance               | -                                                                                 |
| Operating temperature    | 0° ~ +40 °C K                                                                     |
| Dimmer                   | No dimmerable, On-Off                                                             |
| Power output             |                                                                                   |
| Power supply             | Necessario, separato, non incluso<br>SI (solo personale qualificato), elettronico |
| Recessed specifications  | -                                                                                 |
| Load resistance          | -                                                                                 |
| Adjustability            | 90°-320°                                                                          |
| Front protection index   | -                                                                                 |
| Accessories not included | Accessori opzionali: filtro honeycomb 40 mm                                       |

## Source info

|                        |                      |
|------------------------|----------------------|
| Integrated source      | Modulo LED integrato |
| Repleaceable source    | Sì                   |
| Power                  | 16W                  |
| Emission               | Diretta              |
| Max consupction        | max 16 W             |
| Features LED           | LED COB CITIZEN      |
| CCT                    | 3000 K               |
| Duration LED (t. 25°C) | -                    |
| CRI                    | 90                   |
| SDCM                   | 3                    |
| Light beam             | 30°                  |
| UGR Maximum            | -                    |
| Light beam flux        | 1500 lm              |
| Useful light flux      | 1260 lm              |
| Photobiological risk   | 1                    |
| Standby power          | -                    |