
Lika

rev. 14-01-2022





General info

DECORATIVO - Ceiling

Family of recessed rectangular LED modules in die-cast aluminium, painted black or white with polycarbonate reflector. Modules available with five lenses. Specially designed to avoid glare (UGR <16).

Ean	8021696267821
Item	LIKA SURFACE 12W 4000K BK
Installation	Ceiling
Guarantee	5 years
Gross weight	0.45 kg
Volume	0.00108 m^3

Technical info

Net weight	0.37 kg
Insulation class	II
Protection index	IP20
Compliance	-
Operating temperature	-
Dimmer	No dimmerable, On-Off
Power output	
Power supply	Integrato, incluso
	SI (solo personale qualificato), elettronico
Recessed specifications	-
Load resistance	-
Adjustability	-
Front protection index	-
Accessories not included	-

Source info

Integrated source	Modulo LED integrato
Repleaceable source	Sì
Power	12,5W
Emission	Diretta
Max consuption	max 12,5 W
Features LED	LED SMD OSRAM
CCT	4000 K
Duration LED (t. 25°c)	-
CRI	90
SDCM	-
Light beam	44°
UGR Maximum	<16
Light beam flux	1250 lm
Useful light flux	700 lm
Photobiological risk	-
Standby power	-

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com