Product data sheet
Characteristics

MGU66.006.0M3
Unica Top - cover frame - 3 gangs, H71 - wengue/ aluminium



Main

Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Top
Number of gangs	3 gangs horizontal
Fixing mode	Clip-in
Cover frame colour tint	Wengue
Decoration colour	Aluminium

Complementary

Material	ASA + PC decorative frame ASA + PC intermediate part Zamak cover frame
Standards	EN 60669-1
Height	80 mm
Width	232 mm
Depth	14 mm
Distance between centers	71 mm
Product weight	0.092 kg
Market segment	Residential Small commercial

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0610 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructio	Need no specific recycling operations

Contractual warranty

Period	18 months