



Main

Range of product	Sedna
Range	Sedna
Product or component type	Switch
Switch function	1-pole
Device presentation	Without frame
Rated current	10 AX - 250 V AC
Cover plate colour tint	White
Connections - terminals	Screwless terminals

Complementary

Power range	2300 W
Wiring device mounting	Flush
Number of cables	2 x 2.5 mm ²
Cable stiffness	Flexible Rigid
Wire stripping length	12 mm
Material	Thermoplastic ABS-UV stabilised
Surface finish	Glossy
Fixing mode	Claws, span of claws working range : 51...80 mm Screws
Height	71 mm
Width	71 mm
Depth	42 mm
Projecting depth	12 mm
Product weight	0.07237 kg

Environment

Standards	IEC 60669-1
Quality labels	CE
Product certifications	GOST-R
IP degree of protection	IP44

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1126 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------