



Main

Range of product	Odace
Range	Odace
Product or component type	Presence detector
Device presentation	Mechanism with fixing frame
Colour tint	White (RAL 9003)
Provided equipment	Supplied with claws
Load type	40...350 W for 230 V AC incandescent lamp 40...350 W for 230 V AC halogen lamp
Type of packing	Paint cover
Wiring device additional information	Manual override with push-buttons NC

Complementary

[Ue] rated operational voltage	230 V AC 50 Hz
Protection type	Fuse protection
Movement detection area	10 x 20 m (PIR mounting height 1.2 m)
Presence detection area	10 x 18 m (PIR mounting height 1.2 m)
Detection angle	112°
Selection modes	A: automatic M: manual
Light intensity adjustment	5...1000 lux
Time delay range	5 s...20 min
Time delay	5 s...20 min
Wiring configuration	2-wire
Number of pin in parallel	40 W for 1 PIR in parallel 50 W for 2 PIR in parallel 80 W for 3 PIR in parallel
Connected auxiliaries	Maximum 3 detectors in parallel for a load
Number of terminals	2 screw terminals

Shape of screw head	Pozidriv No 1
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² solid cable(s) 1 x 1.5...2 x 2.5 mm ² stranded cable(s) 1 x 1.5...2 x 2.5 mm ² flexible cable(s)
Wire stripping length	8 mm
Material	ABS (acrylonitrile butadiene-styrene) centre plate PA6 inlay PC (polycarbonate) GF10 technical cover PA (polyamide) 6 GF20 FR monobloc
Device mounting	Flush
Fixing mode	By screws By claws
Mounting height	1...1.4 m
Height	71 mm
Width	71 mm
Depth	50.3 mm
Embedding depth	32 mm
Product weight	0.0822 kg
Targeted channel	Professional

Environment

Derating factor	With power derating 5 W per °C above 25 °C
IP degree of protection	IP20
IK degree of protection	IK04
Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-5...50 °C
Standards	EN 61000-6-2 2004/108/EC EN 60669-2-1 2006/95/EEC

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available  End of life manual
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------